

Product Data Sheet 7214 N/17

**ebmpapst**

The engineer's choice



7214 N/17

## INDEX

|          |                                    |          |
|----------|------------------------------------|----------|
| <b>1</b> | <b>General</b> .....               | <b>3</b> |
| <b>2</b> | <b>Mechanics</b> .....             | <b>3</b> |
| 2.1      | General.....                       | 3        |
| 2.2      | Connections.....                   | 3        |
| <b>3</b> | <b>Operating Data</b> .....        | <b>4</b> |
| 3.1      | Electrical Operating Data .....    | 4        |
| 3.2      | Electrical Interface - Output..... | 5        |
| 3.3      | Electrical Features .....          | 5        |
| 3.4      | Aerodynamics .....                 | 7        |
| 3.5      | Sound Data.....                    | 8        |
| <b>4</b> | <b>Environment</b> .....           | <b>8</b> |
| 4.1      | General.....                       | 8        |
| 4.2      | Climatic Requirements .....        | 8        |
| <b>5</b> | <b>Safety</b> .....                | <b>9</b> |
| 5.1      | Electrical Safety .....            | 9        |
| 5.2      | Approval Tests .....               | 9        |
| <b>6</b> | <b>Reliability</b> .....           | <b>9</b> |
| 6.1      | General.....                       | 9        |

**1 General**

|                                     |                        |  |
|-------------------------------------|------------------------|--|
| Fan type                            | Fan                    |  |
| Rotating direction looking at rotor | Counterclockwise       |  |
| Airflow direction                   | Air outlet over struts |  |
| Bearing system                      | Ball bearing           |  |
| Mounting position - shaft           | Any                    |  |


**2 Mechanics**

**2.1 General**

|   |   |  |
|---|---|--|
| Depth   | 55,0 mm   |  |
| Diameter  | 150,0 mm  |  |
| Mass  | 0,725 kg  |  |
| Housing material                                      | Metal   |  |
| Impeller material                                     | Plastic   |  |
| Max. torque when mounted across both mounting flanges | Wire outlet corner: 560 Ncm<br>Remaining corners: 560 Ncm               |  |
| Screw size  | ISO 4762 - M4 degreased, without an additional brace and without washer |  |

**2.2 Connections**

|                       |             |  |
|-----------------------|-------------|--|
| Electrical connection | Wires       |  |
| Lead wire length      | L = 365 mm  |  |
| Tolerance             | + - 10,0 mm |  |
| Tube length           | S = 10 mm   |  |
| Tolerance             | + - 5,0 mm  |  |



| Wire | Color | Operation | Wire size | Insulation diameter |
|------|-------|-----------|-----------|---------------------|
| 1    | red   | + UB      | AWG 22    | 1,7 mm              |
| 2    | blue  | - GND     | AWG 22    | 1,7 mm              |
| 3    | white | Alarm     | AWG 22    | 1,7 mm              |

The auxiliaries shown on the schematic diagram (which are required for the intended use) are not part of our delivery.

### 3 Operating Data

#### 3.1 Electrical Operating Data

Measurement conditions: Normal air density = 1,2 kg/m<sup>3</sup>; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified). In the intake and outlet area should not be any solid obstruction within 0,5 m.

$\Delta p = 0$ : corresp. to free air flow (see chapter aerodynamics)  
I: corresp. to arithm. mean current value

Note:


No inrush current at Unom means:

The internal electrolytic capacitor 120uF/50V has no resistor or inrush current limitation, essentially the power supply and the type and length of the connecting cable is limiting the Inrush current.

| Features                     | Condition      | Symbol         | Values      |             |             |
|------------------------------|----------------|----------------|-------------|-------------|-------------|
| Voltage range                |                | U              | 12 V        |             | 30,0 V      |
| Nominal voltage              |                | U <sub>N</sub> |             | 24,0 V      |             |
| Power consumption            | $\Delta p = 0$ | P              | 6,0 W       | 12 W        | 22 W        |
| Tolerance                    | 0010           |                | +/- 20,0 %  | +/- 20,0 %  | +/- 20,0 %  |
| Current consumption          | $\Delta p = 0$ | I              | 335 mA      | 500 mA      | 615 mA      |
| Tolerance                    | 0010           |                | +/- 20,0 %  | +/- 20,0 %  | +/- 20,0 %  |
| Speed                        | $\Delta p = 0$ | n              | 2.500 1/min | 3.050 1/min | 3.620 1/min |
| Tolerance                    | 0010           |                | +/- 10,0 %  | +/- 7,5 %   | +/- 10,0 %  |
| Starting current consumption |                |                |             | 2.300 mA    |             |


### 3.2 Electrical Interface - Output

|            |                                 |
|------------|---------------------------------|
| Alarm type | /17 (high = ok, open collector) |
|------------|---------------------------------|



$$R_a = \frac{U_{BA} - U_{A\text{low}}}{I_{\text{sink}}}$$

Lüfter / Fan      Kunde / Customer




- 1) Wenn der Lüfter abgeschaltet ist, hängt der Zustand des Ausgangssignals  $U_A$  von der Kundenapplikation ab.  
*When the fan is powered off, the output signal  $U_A$  depends on the customer's application.*
- 2) Für den gültigen Zustand (a oder b) siehe Alarmunterdrückung in der Tabelle.  
*For the valid condition (a or b) see alarm suppression in the table.*

| Features                  | Note  | Values                |
|---------------------------|---|-----------------------|
| Alarm operating voltage   | $U_{BA}$  | $\leq 60,0 \text{ V}$ |
| Alarm signal Low          | $U_{A\text{low}}$   | $\leq 0,6 \text{ V}$  |
| Alarm signal High         | $U_{A\text{high}}$  | $60 \text{ V}$        |
| External resistor         | External resistor $R_a$ from $U_{BA}$ to $U_A$ required. All voltage measured to GND. |                       |
| Alarm start-up delay time | $t_6$   | 5,0 s                 |
| Tolerance                 |   | + - 2,0 s             |
| Alarm delay time          | $t_7$   | 1,0 s                 |
| Tolerance                 |   | + - 1,0 s             |
| Alarm trip speed limit    | $n_G$   | 1.800 1/min           |
| Tolerance                 |   | + - 100 1/min         |

### 3.3 Electrical Features

|                                |                       |  |
|--------------------------------|-----------------------|--|
| Electronic function            | None                  |  |
| Reversed polarity protection   | Rectifying diode      |  |
| Max. residual current at $U_N$ | $I_F < 10 \text{ mA}$ |  |
| Locked rotor protection        | Auto restart          |  |

|                               |                                     |  |
|-------------------------------|-------------------------------------|--|
| Locked rotor current at $U_N$ | $I_{\text{block}}$ approx. 2.100 mA |  |
| Clock signal at locked rotor  | $t_3 / t_4$ typical: 1,4 s / 5,3 s  |  |



### 3.4 Aerodynamics

Measurement conditions:

Measured with a double chamber intake rig acc. to DIN EN ISO 5801.

Normal air density = 1,2 kg/m<sup>3</sup>; Temperature 23°C +/- 3°C;


In the intake and outlet area should not be any solid obstruction within 0,5 m. Motor shaft horizontal.

The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions.

a.) Operation condition:

3.050 1/min at free air flow

|   |                         |  |
|---|-------------------------|--|
| Max. free-air flow ( $\Delta p = 0 / \dot{V} = \text{max.}$ )   | 345,0 m <sup>3</sup> /h |  |
| Max. static pressure ( $\Delta p = \text{max.} / \dot{V} = 0$ ) | 160 Pa                  |  |



**3.5 Sound Data**

Measurement conditions: Sound pressure level: 1 meter distance between microphone and the air intake.  
 Sound power level: Acc. to DIN 45635 part 38 (ISO 10302)  
 Measured in a semianchoic chamber with a background noise level of  $L_p(A) < 5 \text{ dB(A)}$   
 For further measurement conditions see chapter aerodynamics.

a.) Operation condition:

|   |                                 |  |
|---|---------------------------------|--|
| 3.050 1/min at free air flow                                    |                                 |  |
| Optimal operating point   | 220,0 m <sup>3</sup> /h @ 50 Pa |  |
| Sound power level at the optimal operating point                | 6,2 bel(A)                      |  |
| Sound pressure level at free air flow, measured in rubber bands | 53,0 dB(A)                      |  |

**4 Environment**

**4.1 General**

|  |        |  |
|--|--------|--|
| Min. permitted ambient temperature TU min. | -25 °C |  |
| Max. permitted ambient temperature TU max. | 72 °C  |  |
| Min. permitted storage temperature TL min. | -40 °C |  |
| Max. permitted storage temperature TL max. | 80 °C  |  |

**4.2 Climatic Requirements**

|                       |   |  |
|-----------------------|---|--|
| Humidity requirements | humid heat, constant; according to DIN EN 60068-2-78, 14 days |  |
| Water exposure        | None  |  |
| Dust requirements     | None  |  |
| Salt fog requirements | None  |  |

Permitted application area:

The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)

There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.

Please require severity levels and specification parameters from the responsible development departments.



## 5 Safety

### 5.1 Electrical Safety

|  |                  |  |
|--|------------------|--|
| Dielectric strength<br>DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700)<br>A.) Type test<br>Measuring conditions: After 48h of storage at 95% R.H. and 25°C.<br>No arcing or breakdown is allowed!<br>All connections together to ground. | 500 VAC / 1 Min. |  |
| B.) Routine test<br>Measuring conditions: At indoor climate.<br>No arcing or breakdown is allowed!<br>All connections together to ground.  | 850 VDC / 1 Sec. |  |
| Isolation resistance<br>Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.   | RI > 10 MOhm     |  |
| Clearance / creepage distance  | 1,0 mm / 1,2 mm  |  |
| Protection class   | III              |  |

### 5.2 Approval Tests

|     |   |   |
|-----|---|---|
| CE  | EC Declaration of Conformity  | Yes   |
| EAC | Eurasian Conformity   | Yes   |
| UL  | Underwriters Laboratories   | Yes / UL audited by CSA according to UL507, Electric Fans                     |
| VDE | Association for Electrical, Electronic and Information Technologies | Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment |
| CSA | Canadian Standards Association                                      | Yes / C22.2 No. 113 Fans and Ventilators                                      |
| CCC | China Compulsory Certification                                      | Not applicable  |


## 6 Reliability

### 6.1 General


|  |           |  |
|--|-----------|--|
| Life expectancy L10 at TU = 40 °C                  | 80.000 h  |  |
| Life expectancy L10 at TU max.                     | 37.500 h  |  |
| Life expectancy L10 acc. to IPC 9591 at TU = 40 °C | 135.000 h |  |

Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

Schutzmerk nach DIN ISO 1676 beachten!  
Refer to protection notice DIN ISO 1676!



Blasrichtung /  
blowing direction



|                                      |                     |                              |  |                    |   |
|--------------------------------------|---------------------|------------------------------|--|--------------------|---|
| SW-Stand/Date                        | Rev. Nr./Change No. | Art.-Nr./System-Nr./Item No. | ebmpapst<br>CAD-Engineering<br>CAD-Engineering | Werkstoff/Material | Volumen/Volume (mm <sup>3</sup> )<br>Gewicht/Weight (g) |
|                                      |                     |                              | Name/Name<br>Artikel/Title                     |                    |   |
| Toleranzen/Tolerances:               |                     | Beach./<br>Drawn/<br>Checked |  |                    |   |
| Allgemeintoleranzen/Gen. tolerances: |                     | Freig./<br>Released          |  |                    |   |
| <b>ebmpapst</b>                      |                     |                              |  |                    |   |
| ebm-papst St. Georgen GmbH & Co. KG  |                     |                              |  |                    |   |
|                                      |                     | Zug-/Nr./Drawing-No.         |  | Teilname/Part/Part | Ers./Zugl./Replaces                                     |
|                                      |                     | Diam./Type of Mount          |  | Teil-Nr./          | Maßstab/Scale   |

1) = Anzahl und Länge der Litzen sowie Länge des Schlauches s. Produkt Spezifikation Bl.3 /  
length and number of wires and length of tube see product specification page 3  
2) = Maße für Montagewand / dimensions for mounting wall